

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
12 January 2006 (12.01.2006)

PCT

(10) International Publication Number
WO 2006/003641 A1

(51) International Patent Classification⁷: A45D 26/00, B26B 19/00

(74) Agents: FENSTER, Paul et al; FENSTER & COMPANY, INTELLECTUAL PROPERTY 2002 LTD., P. O. BOX 10256, 49002 PETACH TIKVA (IL).

(21) International Application Number:
PCT/IL2004/000602

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW

(22) International Filing Date: 6 July 2004 (06.07.2004)

(25) Filing Language: English

(26) Publication Language: English

(63) Related by continuation (CON) or continuation-in-part (CIP) to earlier application:
US PCT/IL03/002 19 and (CIP)
Filed on 13 March 2003 (13.03.2003)

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (for all designated States except US): RADIANCY INC. [US/US]; 40 RAMLAND ROAD SOUTH, ORANGEBURG, New York 10962 (US).

(72) Inventors; and


(75) Inventors/Applicants (for US only): AZAR, Zion [IL/IL]; 17 NURIT STREET, 73142 SHOHAM (IL). SHALEV, Pinchas [IL/IL]; 13 KDUMIM STREET, 44244 KFAR SABA (IL).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: ELECTRIC SHAVER WITH DEBRIS REMOVAL ELEMENT



(57) Abstract: A hair cutting head 605, for use in a hair cutting apparatus 500 comprising: an elongated heated wire 260 suitable for shaving, cutting or burning hair growing from a skin surface; and a blunt debris removal element 650, situated and configured to remove debris or scorched hair residue from the skin after shaving, cutting or burning by the heated wire.

WO 2006/003641 A1

ELECTRIC SHAVER WITH DEBRIS REMOVAL ELEMENT RELATED APPLICATIONS

The present application is a continuation-in-part of PCT/IL03/00219, PCT/IL03/00220, and PCT/EL03/00221 all filed on March 13, 2003, the disclosures of which are incorporated
5 herein by reference.

FIELD OF THE INVENTION

The present invention relates to removing hair with a heat element.

BACKGROUND OF THE INVENTION

The removal of unwanted hair from the body can be accomplished with mechanized
10 means, for example razors, tweezers or wax, all of which are uncomfortable to use, irritate the skin and/or cause damage to the skin.

The use of heated wires or other structures to cut hair from a skin surface has been proposed. However, a heat generator that generates heat of a sufficient magnitude to cut hair and is offset from the skin to prevent skin damage, often leaves behind unwanted stubble.

15 In Peterson, US 3,934,115, parallel metal strips on the upper side of ceramic facing that contacts the skin, are used to cut hair. Hills, in US 2,727,132 and P. Massimo in IT 1201364, use a continuously heated element to burn hair. P.M. Bell in US 558,465, D. Seide in US 0,589,445, G.S. Hills in US 2,727,132, G.L. Johnson in US 3,093,724, Hashimoto in US 5,064,993 and US 6,307,181 B1, F. Solvinto in FR 2531655 and EP 0201 189, and E. Michit in
20 2612381, use a continuously heated wire to burn hair. J.F. Carter in US 3,474,224, provides a circular comb device for burning nose hairs. These references do not appear to provide a means of reducing the hairs to the level of the skin.

Vrtaric, in US 4,254,324, provides a heat hair cutting system that is applied only to the tips of the hair to remove the split ends.

25 Iderosa, in US 5,065,515, describes a heating element that preheats hair before cutting it with a blade coupled to the heating element. However, since the heating element is permanently in contact with the skin, it is believed that its temperature is limited to a temperature which does not damage the skin, for continuous exposure and which is not uncomfortable for the user.

The present applicants have disclosed a heat-generating system for cutting hair in PCT
30 publications WO 03/009977 and WO 03/009976. The disclosures of these applications are incorporated herein in their entirety by reference. These applications describe methods and devices in which a wire providing pulsed or non-pulsed heat is used to cut hair. As used herein, a heat-generating wire refers to one or more of: metal wires, ribbons or any other type of heat-

generating elements capable of generating heat of sufficient magnitude and/or duration to cut hair from an area of skin. In general, all of the configurations of wires, etc. disclosed in either of the above referenced applications are applicable to the present invention, hi addition, the structures and methods described herein are usable in or in conjunction with the structures disclosed therein.

In the above referenced PCT applications, the hair is severed close to the skin by heating the hair. This severing of the hair may also destroy at least a portion of the hair below the skin. As used herein the term "cut" is used to describe this type of severing or shaving of the hair.

SUMMARY OF THE INVENTION

An aspect of some embodiments of the invention relates to a structure adapted for cutting hair with a removable cutting head. The removable cutting head comprises a wire that generates heat that is sufficient to cut hair, optionally with the aid of a blade, hi an exemplary embodiment of the invention, the removable cutting head is positioned in the structure between two supports that position the surface of the skin with respect to the wire.

Optionally, one of the supports is adapted to sense motion of the structure across the skin from which the hair grows, for example using a movable roller, an optical motion detector or an inertial motion detector. In some embodiments of the invention, the cutting head is activated responsive to the motion. In some embodiments of the invention, the cutting head is positioned to contact the skin and is activated to cut hair by heating the wire. Alternatively, the cutting head is normally positioned below the supports (out of contact with the skin) and when activated, is moved to the level of the supports to interface the skin.

In some embodiments of the invention, the wire is heated only when motion is detected by the support sensor, in order to prevent the skin from being burnt by contact with the wire for a long time. Alternatively, the wire is distanced from the skin when not in motion across the skin, hi the latter case, the heating need not be controlled by the sensing of motion.

An aspect of some embodiments of the invention relates to a removable cutting head for cutting hair by heat that comprises a debris removal element, such as a blunt scraper, to remove debris resulting from the cutting process, hi an exemplary embodiment of the invention, the cutting head burns hairs near their roots leaving carbonized residue in the hair pores and on the skin surface. The scraper, optionally attached to the cutting head, scrapes away the carbonized residue and any other debris (e.g. small hairs) produced during the cutting process.

An aspect of some embodiments of the invention relates to a removable cutting head for cutting hair by heat, which additionally comprises a blade mounted on one side of the cutting head, hi some embodiments of the invention, the wire in the cutting head is not hot enough to cut hair, or is not hot enough to cut hair with a thickness above a certain value. In this case, the blade cuts the hair. However, heating of the hair makes the cutting action faster and smoother even without shaving cream or the like. Optionally, the blade mounted on the cutting head complements the heated wire in cutting hair, leading to a smoother result. In some embodiments of the invention, the heated wire softens the hair before it is cut, in order to allow use of a duller blade. In an embodiment of the invention, the wire is heated to a temperature 50 to 100°C, optionally between 100 to 150°C, 150 to 250°C, 250 to 500°C or 500 to 600°C. While this aspect of the invention is usable with wires that are not hot enough to burn and cut the hair, it is also usable with hotter wires which do cut some or all the hairs and is then used as a back-up to avoid multiple passes for cutting uncut or partially cut hairs.

There is thus provided, in accordance with an embodiment of the invention, a hair cutting head, for use in a hair cutting apparatus comprising:

an elongated heated wire suitable for shaving, cutting or burning hair growing from a skin surface; and

a blunt debris removal element, situated and configured to remove debris or scorched hair residue from the skin after shaving, cutting or burning by the heated wire.

Optionally, the head comprises a row of skin depressing elements on at least one side of said elongated heated wire. Optionally, the at least one side is opposite a side on which the blunt debris removal element is situated.

Optionally, the wire has a diameter between 10 to 1000 micrometers, optionally, between 10 to 500 micrometers or between 500 to 1000 micrometers.

There is further provided, in accordance with an embodiment of the invention, a hair cutting device comprising:

a hair cutting head according to any of the preceding claims; wherein said wire is heated when said cutting head comes in contact with a skin surface.

In various embodiments of the invention, the wire is heated to a temperature between 700 and 800°C, 800 and 1000°C or more than 1000°C.

BRIEF DESCRIPTION OF THE DRAWINGS

Exemplary non-limiting embodiments of the invention described in the following description, read with reference to the figures attached hereto, hi the figures, identical and

similar structures, elements or parts thereof that appear in more than one figure are generally labeled with the same or similar references in the figures in which they appear. Dimensions of components and features shown in the figures are chosen primarily for convenience and clarity of presentation and are not necessarily to scale. The attached figures are:

5 Fig. 1A is a schematic diagram of a structure supporting a heat-generating wire adapted for cutting hair, in accordance with an exemplary embodiment of the invention;

Fig. 1B is a schematic diagram of an alternative structure of Fig. 1A, in accordance with an exemplary embodiment of the invention;

10 Fig. 2 is a schematic diagram of the structure of Fig. 1A including position adjusters, in accordance with an exemplary embodiment of the invention;

Fig. 3 is a partly sectioned isometric view of a vibrating hair cutting unit, in accordance with an exemplary embodiment of the invention;

Fig. 4 is a side cross-section of the vibrating hair cutting unit of Fig. 3, shown while cutting a hair, in accordance with an exemplary embodiment of the invention;

15 Fig. 5A is a schematic diagram of a hair cutting unit without a shaving head according to an exemplary embodiment of the invention;

Fig. 5B is a schematic diagram of a hair cutting unit with a removable shaving head deployed to contact the skin, according to an exemplary embodiment of the invention;

20 Fig. 5C is a schematic diagram of a hair cutting unit with a removable shaving head deployed at a distance from the skin, according to an exemplary embodiment of the invention;

Fig. 6A is a schematic diagram of a removable shaving head, according to an exemplary embodiment of the invention;

Fig. 6B is a schematic diagram of an alternative removable shaving head, according to an exemplary embodiment of the invention; and

25 Fig. 6C is a schematic diagram of an additional alternative removable shaving head, according to an exemplary embodiment of the invention.

DESCRIPTION OF EXEMPLARY EMBODIMENTS

30 Fig. 1A is a simplified schematic diagram of a heat-generating wire 260 suspended on a frame 200, comprising two posts 240 and 242, in accordance with an exemplary embodiment of the invention. In an exemplary embodiment, posts 240 and 242 comprise wire guideways 120 and 122. Heat-generating wire 260 is optionally centered in guideways 120 and/or 122.

In an exemplary embodiment, posts 240 and 242 are held in position by a strut 244, for example substantially perpendicular to posts 240 and 242. Heat-generating wire 260, for example, is attached at wire ends 270 and 272 to posts 240 and/or 242.

In an exemplary embodiment, a conduction post 290 is electrically conductive and is attached to an electrically conductive area 190 while a conduction post 292 is electrically conductive and is attached to an electrically conductive area 192. Further, tension-providing posts 240 and 242 are electrically conductive and connected to conductive areas 190 and 192 respectively so that power provided through posts 290 and 292 causes wire 260 to generate heat.

In an exemplary embodiment, one or both of tension posts 240 and 242 are manufactured from a springy electrically conductive material so that when properly positioned, they serve to keep heat-generating wire 260 taut during motion across a skin surface. Optionally, posts 240 and/or 242 are relatively flexible so they bend when subjected to a force pushing them towards each other. Optionally, posts 240 and/or 242 are relatively inflexible so they do not bend when subjected to a force pushing them perpendicular to the axis of wire 260.

In an exemplary embodiment, tensioning of wire 260 during manufacture is accomplished, for example, in the following manner, when one or both of the posts are springy.

With the wire placed in guides 120 and 122, wire ends 270 and/or 272 are pulled in a direction 208, with sufficient force and/or at an appropriate angle, with respect to (horizontal) wire 260, to cause posts 240 and 242 to bend toward each. Wire 260 is then attached to posts 240 and/or 242, for example at points 276 and 278 respectively, using solder, electrically conductive glue (such as conductive epoxy), brazing, laser brazing and/or other connection means known in the art. Mechanical connection such as clamping can also be used. Optionally the clamp is copper or gold coated to provide a slightly conforming and highly conductive mechanical electrical connection. It should be noted that posts guideways 120 and/or 122 may be continually bent toward each other by the tension of wire 260. After attachment to the posts, free ends of the wires may be removed.

A similar method may be used if only one post is springy (or even if both are springy). In this case, wire 260 is optionally permanently attached to the inflexible post (or optionally to the frame), before or after tensioning. Then the other end of the wire is tensioned as aforesaid and then attached to the frame or post on which it is mounted. Optionally, especially when the wire is pre-attached to one of the posts, that post does not need a guide.

Optionally, additional tension to wire 260 is provided by one or more coiled springs between posts 240 and/or 242 and wire 260.

5 Tensioned wire 260 will remain in tension even in the presence of longitudinal expansion that occurs due to heating of wire 260 and/or due to pressure as wire 260 moves in a direction 402 against a hair 404 (Fig. 4).

One method of pulling wire ends 270 and/or 272 in direction 208 is by attaching wire ends 270 and/or 272 to one or more tension-providing wheels (not shown), positioned, for example on strut 244. By rotating the one or more wheels, wire ends 270 and 272 are pulled in direction 208 to tension wire 260. Other methods for pulling wire 260 in direction 208 are
10 known in the art and include, for example, attaching a spring mechanism and/or pneumatic tensioning device to wire ends 270 and/or 272.

In an exemplary embodiment, conductive post 290 fits into a socket 180 and conductive post 292 fits into a socket 182. A friction fit between sockets 180 and 182 and posts 290 and 292 is provided, for example to allow easy removal of frame 200 from sockets 180 and 182 for
15 replacement of the entire frame or for cleaning and/or repair of wire 260. Sockets 180 and 182, for example, are conductive and capable of transmitting power from a power source, thereby providing electrical current to heat-generating wire 260 via posts 290 and 292, connection area 190 and 192 and tension posts 240 and 242. It is generally envisioned that the wire, posts and strut mechanism will be replaced when the wire breaks.

20 In an exemplary embodiment, post supports 160 are positioned against posts 240 and 242 to prevent undue motion in a direction 168. Alternatively or additionally, posts supports 162 are positioned against posts 240 and 242 to prevent undue motion in a direction 166. This assures that motion applied to frame 200 results in desired motion of the wire.

Fig. 1B is a schematic diagram of an alternative structure of Fig. 1A, in accordance with
25 an exemplary embodiment of the invention. In this embodiment, wire 260 passes through rings 150 and 152 in posts 240 and 242 prior to tensioning and attachment to the posts.

Fig. 2 is a schematic diagram of heat-generating wire 260 on frame 200 of Fig. 1A, mounted in vibrating compartment 300 that projects from vibrator posts 130 and 138. In an exemplary embodiment, a vibrator 350 connected to posts 130 and 138, comprises a motor 234
30 having an off-center weight 232 that causes vibration of vibrator 350 as motor 234 revolves in a direction 230. Alternatively or additionally, vibrator 350 is connected to posts 130 and 138 with a transverse connector 354.

An optional cross pin 132 passes through vibrator posts 130 and 138, allowing their movement around pin 132. As vibrator 350 vibrates, it imparts vibration to vibrator posts 130 and 138, thereby causing heat-generating wire 260 and/or compartment 300 to cyclically move in directions 402.

5 In cutting hair 404 (Fig. 4), vibration of wire 260, frame 200 and/or compartment 300 facilitates heat-generating wire 260 to make multiple passes over hair 404 while held against a given area of skin 400. Multiple passes of wire 260 increase the cutting efficiency of heat-generating wire 260 during each period it contacts area of skin 400 (i.e., as it is moved, by the user, across the skin surface). The excursion of the wire is, for example, between 0.05 and 2
10 mm, optionally between 0.3 and 1 mm.

In an exemplary embodiment, vibrating compartment 300, for example comprises a snap-together structure and/or is removably attached to vibrator posts 130 and 138 so that it can be removed for cleaning and/or to allow removal of frame 200 from sockets 180 and 182.

As shown more clearly in Fig. 3, in an exemplary embodiment, compartment 300
15 comprises a row of skin-depressing elements 312. Skin-depressing elements 312 serve to depress and/or tighten area of skin 400 (Fig. 4), allowing heat-generating wire 260 to cut hair 404 without sinking into skin 400 and possibly dissipating its heat so that it cuts less efficiently and/or burns skin 400.

In an exemplary embodiment of the invention, two rows of skin-depressing elements
20 are provided on either side of heat-generating wire 260. Rows of skin depressors are shown in the PCT publications described above, for example, posts or the like. However, the skin depressors shown in the present embodiments differ from those shown in that they comprise elongate elements that whose long axis points generally toward the wire. The present inventors have found that the elongate elements shown herein provide for smoother and more
25 comfortable travel of the shaver along the skin. Other configurations of skin-depressing elements 312, for example, comprising skin-depressing elements 312 at varied heights, angles, and/or planes with respect to skin 400 (Fig. 4), wire 260 and/or compartment 300, are also contemplated in exemplary embodiments of the invention. In preferred embodiments of the invention the long axis of the elongate elements is parallel to the plane of the opening (and thus
30 of the skin) or are at a small angle (5, 10, 15 or 20 degrees) with respect to the plane.

Alternatively or additionally, post protectors 340 and 342 extend beyond posts 240 and 242 and/or skin-tensing and depressing elements 312. In an exemplary embodiment, post protectors 340 and 342 prevent the heat and/or vibrations from posts 240 and 242 from

damaging skin 400 (Fig. 4) or vice-versa, by offsetting the proximate area of skin 400 proximal away from posts 240 and 242.

In an exemplary embodiment, wheels 318, 320 and/or 330 are juxtaposed against strut 244 and are rotatable so that flats 388, 390 and 392 respectively adjust the position of strut 244. Positional adjustments of strut 244 affect the position of wire 260 with respect to skin-depressing elements 312 and hence against area of skin 400. By rotating wheels 318, 320 and/or 330, an operator, for example, controls the closeness of heat-generating wire 260 to skin-depressing elements 312, adjusting the position of wire 260 in a direction 248. Alternatively or additionally, the operator adjusts the angle of wire 260 to skin-depressing elements 312, for example in directions 284 and/or 286.

Using wheels 318, 320 and/or 330 an operator can optimally position an angle of the wire with respect to the plane of the ends of depressors 312 (or the opening, if rows of depressors are not used).

Fig. 3 is a cross-section of a vibrating hair cutting unit 100 having vibrating compartment 300 and a relatively non-vibrating structure 106, with wire 260 positioned within a gap 328. Optionally, skin-depressing elements 312 are elongate elements, positioned on one side of wire 260, pointing toward gap 328. As indicated above, a row of skin depressing elements 314 may comprise elongate elements on the opposite side of wire 260 gap that point toward gap 328. Optionally, post supports 160 and 162 are positioned against posts 240 and 242 to prevent wire 260 from contacting skin depressing elements 312 and/or 314.

Structure 106, for example, comprises a mechanical motion detector wheel or roller 110 that rotates along a surface, for example area of skin 400 (Fig. 4) and signals a controller 118 that unit 100 is moving in relation to skin 400. In an exemplary embodiment, controller 118 turns vibrator 350 on or off in response to movement, thereby causing vibrator 350 to selectively provide vibrations.

Optionally, motion detector wheel 110 switches vibrator 350 on when unit 100 moves above a minimum speed in relation to skin 400 and switches vibrator 350 off when unit 100 moves below the minimum speed. In exemplary embodiments of the invention, the minimum speed is between 0.2 to 1 cm/second optionally about 0.5 cm/sec. In some embodiments of the invention, the motion detector also indicates when the speed is above a value to cause proper hair removal. In general, this speed is above 1-3 cm/sec. However, this value may vary depending on the diameter and temperature of the wire. Alternatively or additionally, mechanical motion detector 110 comprises an optical motion detector that directs controller

118 to switch vibrator 350 on or off. Optionally, in addition to controlling vibrations, motion detector 110 functions to switch heat generated by wire 260 on or off in response to motion of unit 100 on skin 400. Optionally, the system includes a visual indication of whether the heat and/or vibration are activated, as for example a light. In an embodiment of the invention, the light is green when the velocity is in a desired range and red when it is outside this range.

In an exemplary embodiment, a battery 114, for example, provides power to vibrator 350 and/or wire 260. Optionally, battery 114 is rechargeable and, for example, linked by a power input 116 to an external power source, for example a power converter and/or an AC electric power receptacle (not shown). Alternatively or additionally, power input 116 is directly connected to wire 260 and/or vibrator 350 without battery 114 intervening and wire 260 is powered, for example, by AC current.

For clarity of presentation, in these embodiments, connections, for example between tension posts 240 and 242, and/or vibrator 350, and battery 114, are not shown. However in an exemplary embodiment, a simple arrangement of electrical connectors is used to electrify heat-generating wire 260, vibrator 350 and/or other components associated with unit 100.

In an exemplary embodiment, cross pin 132 has end pins 134 and 136 that attach to structure 106, allowing vibrating compartment 300 to vibrate on posts 130 and 138 in relation to structure 106. One or more movement limiters 332 that abut post 130 and/or 138 to limit excursion of posts 130 and 138 during vibration of compartment 300 optionally project from housing 106. In an exemplary embodiment, movement limiters 332 comprise compressible material, for example a silicone. In an alternative exemplary embodiment, frame 200 is connected directly to vibrator 350 and compartment 300 and structure 106 remain stationary while heat-generating wire 260 vibrates in relation to skin 400.

In an exemplary embodiment, compartment 300 comprises a container 140 adapted for receiving a fluid and/or solid deodorant 142. Container 140, for example, is joined to a passage 146 having a venturi opening 148. Deodorant 142 atomizes as compartment 300 vibrates and is distributed through venturi opening 148 to the area around wire 260 and/or to skin 400.

Alternatively or additionally, deodorant 142 vaporizes in response to heat provided by heat-generating wire 260. Alternatively or additionally a cover 310 is provided on passage 146 and a user-operated trigger 308 is provided on structure 106 that opens cover 310 to release vapors and/or aerosol from deodorant 142.

No matter what type of dispensation means is used, though, as deodorant 142 atomizes and/or vaporizes, it passes through communication passage 146 to the general area of heat-

generating wire 260 and skin 400₃ thereby masking and/or neutralizing odors generated during cutting of hair. The deodorant (which can be a perfume that masks the smell of the burnt hair), can be provided in different popular scents

In still another alternative exemplary embodiment shown in Fig. 1A, a smoke and/or odor-removing filter 280 is located over ventilation holes 380 in strut 244. A rotatable ventilator prop blade 236 (or other pumping mechanism) rotates to cause odors to be drawn through filter 280. A ventilator passage connecting an input of filter 280 to holes 380 may be provided to allow flow of the air containing the burnt odor to filter 280

Optionally, filter 280 comprises a porous material that absorbs a deodorant, for example a liquid deodorant and an operator places liquid deodorant on at least one area of filter 280. As odors pass over filter 280, they are neutralized and/or replaced with a pleasant fragrance. Optionally, odor-removing filter 280 is located in or adjacent a receptacle 374 that additionally collects cut hair 460 (Fig. 3).

Optionally, blade 236 is activated together with the heat and/or vibration. Optionally, it is deactivated at the same time as one or both of these elements or operates for a somewhat longer time to provide additional odor removal.

Fig. 4 is schematic cross-sectional view of vibrating hair cutting unit 100 cutting hair 404 that is growing from area of skin 400, in accordance with an exemplary embodiment of the invention.

In an exemplary embodiment, an electrostatic outcropping 370 is incorporated into unit 100, for example near motion detector wheel 110 and electrostatically attracts a cut hair 460 cut by heat-generating wire 260. Electrostatic outcropping 370, for example, of Teflon material will self charge, by friction with the skin, to an extent suitable for attracting the hair. Other charging means and materials can also be used.

Optionally, hair collection receptacle 374 is juxtaposed near outcropping 370 to collect cut hair 460 that accumulates on outcropping 370. Optionally, receptacle 374 has a collection aid 378, comprising a comb or brush, that brings cut hair 460 in proximity of outcropping 370.

In an exemplary embodiment, wire 260 is manufactured from Kantaal D, (an alloy of nickel chromium and other metals manufactured by Kantaal Group). Alternative materials for wire 260 include Nichrome, other wire resistance materials or other alloys suitable for high temperature operation. For lower temperatures other spring steel (SS) alloys are suitable. For higher temperatures platinum tungsten wire (such as PtW wire manufactured by Johnson Matthey (UK), Precious Metals Division or Goodfellow (UK)) may be used. Other high

temperature wires materials such as pure platinum and platinum/iridium alloy can also be used. However, such wires are very flexible.

In an exemplary embodiment, the current through wire 260 is 0.5 A, though it may vary, depending on the dimensions and/or materials comprising wire 260. In order to cut efficiently, wire 260, for example, reaches a peak temperature of between 700 and 1200°C₅ when wire 260 is held against hair 404 for 0.1-100 milliseconds, optionally 1-10 milliseconds, depending on the mass and temperature of the wire used. In some embodiments of the invention, the temperature of the wire is even higher than 1200°C.

Lower temperatures, for example 500°C, can be used to cut hair 404 when wire 260 is held against hair for longer periods of times, for example, 50-150 milliseconds. Higher temperatures, for example 1000°C, can be used to cut hair 404 when wire 260 is held against hair 404 for shorter periods of time, for example, 5-15 milliseconds.

Battery 114, for example, produces between 3 and 30 volts and between 0.030 and 5 amperes, depending on the dimensions of wire 260.

In exemplary embodiments, wire 260 has a circular cross section with a diameter of 0.01-0.25 millimeters. Alternatively, wire 260 has a diameter of above 0.25 millimeters (e.g. between 0.25 mm- 0.5 mm or even up to 1 mm), when manufactured from a less flexible and/or weaker material and below 0.25 millimeters when manufactured from a more flexible and/or stronger and/or higher temperature material.

In some embodiments of the invention, wire 260 is shaped as a ribbon with a rectangular cross section or another geometrical shape, instead of a circular cross section as described above. Optionally, the width of the cross section is similar to the diameter of wire 260 with a circular cross section. In some embodiments of the invention, wire 260 has a sharpened head which serves as a blade to assist in removing hairs which did not burn from the heat.

Wire 260 has a length, for example, of 25-30 millimeters though it could have a length greater than 30 millimeters or less than 25 millimeters, based upon, for example, the amount of hairs 404 that it is designed to cut on each pass.

Examples of springy electrically conductive materials used in manufacturing posts 240 and/or 242, include spring steel (SS 302) and beryllium copper. Optionally, the posts are plated with a material such as tin, which improves conductivity to the wire and solderability of the posts.

Skin-depressing elements 312 are shown as being straight comb-like pieces, though their shape could vary. Alternatively or additionally, rows of skin-depressing elements 312 with varied designs could be included in a kit provided with unit 100. For example, rows of skin-depressing elements 312 included in the kit could be curved along their length, semi circular or even end in round balls. Use of the various designs of rows of skin depressors 312 could be based on, for example hair density and/or preference of the operator.

Fig. 5A is a schematic diagram of a hair cutting unit 500 without a shaving head according to an exemplary embodiment of the invention. In an exemplary embodiment of the invention, hair cutting unit 500 comprises an encasement 530 with two support elements (510, 110) installed on the top end that interface the user's skin 400. In an exemplary embodiment of the invention, a socket 540 is provided between the two support elements. Optionally, as shown in Fig. 5B a removable shaving head 600 is deployed into socket 540 between the supports in order to cut hair. In an exemplary embodiment of the invention, one of the supports comprises motion detector wheel 110, which senses movement of the head across a surface with hair and activates hair cutting unit 500. Optionally, the second support comprises a balance roller or fingers 510, which balances hair cutting unit 500 so that removable shaving head 600 will be held tangent to the surface of skin 400 while hair cutting unit 500 is pressed against skin 400 to cut hair. Optionally roller or fingers 510 have only a small contact area (in the transverse direction) with skin surface 400, so that the hair can pass freely to the cutting head.

In an exemplary embodiment of the invention, socket 540 comprises two or more conduction posts 520 upon which removable shaving head 600 is mounted. Optionally, conduction posts 520 supply electrical current to shaving head 600 to heat wire 260. Optionally, the posts can be non-conducting with electrical connection to the cutting head provided by other means.

Fig. 5C shows hair cutting unit 500 with shaving head 600 in a retracted position. As indicated above motion detector wheel 110 is used to detect motion (or other means, for example, an optical motion detector or an inertial motion detector, as known in the art or described in the present inventor's previous PCT publications). When motion is detected, a controller optionally, instructs shaving head 600 to be brought to the position shown in Fig. 5B. When motion is not detected, the shaver head is in the retracted position shown in Fig. 5C.

Fig. 6A is a schematic diagram of removable shaving head 600, according to an exemplary embodiment of the invention. As shown in Fig. 6A shaving head 600 comprises two or more connection sockets 630 which match conduction posts 520 (shown in Fig. 5A).

Optionally, when deployed conduction posts 520 form electrical contact with a connection wire 620 that electrically connects between connection sockets 630 to wire 260.

In some embodiments of the invention, socket 540 and removable shaving head 600 are designed so that removable shaving head 600 is aligned with balance roller 510 and motion
5 detector 110. Optionally, in use of hair cutting unit 500, balance roller 510 and motion detector 110 are pressed against the surface of skin 400 and moved along skin 400 to cut hair. Optionally, motion detector 110 senses the motion and causes hair cutting unit 500 to supply current to heat, wire 260. Skin depressing elements 312 glide along the surface and position the skin surface with respect to wire 260, while the hair is ignited at the point of contact with wire
10 260. Optionally, when hair cutting unit 500 is not in motion, current is not supplied to wire 260 on order to prevent damage to skin 400 from the heat at the parking position.

In some embodiments of the invention, socket 540 is positioned so that removable shaving head 600 is below the supports (as shown in Fig. 5C), balance roller 510 and motion detector 110. Optionally, when motion detector 110 senses motion socket 540 rises up to align
15 the top of shaving head 600 with balance roller 510 and motion detector 110, in order to cut hair. Optionally, when the motion ceases socket 540 sinks down to the original position which prevents contact between wire 260 and skin 400.

In some embodiments of the invention, current is continuously supplied to wire 260, since skin 400 is protected by withdrawal of head 600, when hair cutting unit 500 is not in
20 motion.

In some embodiments of the invention, the current is turned off, for safety sake. It should be understood that in the shavers described in the inventors' prior publications, the thickness (mass) of the wire is limited by the need to cool the wire quickly when the current is turned off, so that the skin does not burn. However, in accordance with the present embodiment
25 of the invention, a thicker wire 260 (e.g. with a diameter of 100-200 micrometers), can be used as compared with the disclosures, since it is taken out of contact with the skin when there is no motion. In addition, the wire can be heated to a higher temperature, since head 600 withdraws when not in motion along the surface of skin 400, thus preventing any specific position from getting burnt. Alternatively or additionally, current may be supplied to the wire as pulses,
30 which are sufficient to burn hair but are short enough to prevent the skin from getting burnt.

In some embodiments of the invention, a Led hole 670 is created at the bottom of removable head 600 to mount a Led or other light source 570 (shown in Fig. 5A) to illuminate

the wire and skin, for example to indicate that hair cutting unit 500 is in use and/or that wire 260 is hot.

hi some embodiments of the invention, socket 540 is vibrated during use in order to enhance the cutting process as described above. However, it should be understood that vibration and other particular features of the described embodiments need not be present in an actual embodiment. In general, each of the features of the present invention may be used with prior disclosed embodiments and can be individually implemented without others of the new features described herein.

Fig. 6B is a schematic diagram of an alternative removable head 605, according to an exemplary embodiment of the invention, hi an exemplary embodiment of the invention, the cutting process using a heated wire 260 may leave debris on the skin and/or in the pores of the hairs, for example as a result of igniting the hairs causing carbonization of the base of the hair in the pore and/or around it. In an exemplary embodiment of the invention, a removable head 605 with a debris removal element 650 (such as a preferably blunt scraper) is used during the cutting process to scrape away debris. Optionally, element 650 is positioned in any other position at which it can scrape the skin after the hair is cut. As used herein, the term "blunt" element means that the element is incapable of cutting hair.

Fig. 6C is schematic diagram of an additional alternative removable head 610, according to an exemplary embodiment of the invention. In this embodiment of the invention, a removable head 610 with a blade 660 is used in order to cut the hair after wire 260 has heated it and enhance the speed of the cutting process. Depending on the wire temperature and mass, wire 260 can cut all or some of the hair, with blade 660 completing the process. Alternatively, for lower temperature of the wire, the hair is not cut through by the wire. However, the heat from wire 260 prepares the hair for cutting (e.g., it softens the hair) so that it is more easily cut. Unlike the prior art device described in the background of the invention, the heated wire can be hot enough to heat the hair to a temperature substantially higher than a temperature that would damage the skin, due to one or more of the low mass of the wire, pulsing of the wire, heating of the wire only when motion is detected and/or the removal of the wire from skin contact when motion is not detected. In some embodiments of the invention, wire 260 may reach temperatures higher than 50°C, 100°C, 150°C or even as high as 1000°C.

A variety of numerical indicators have been utilized to describe the dimensions or temperature of the heat-generating wire. Additionally, a variety of numerical indicators have been utilized to describe structures besides heat-generating wire, including length, diameter and

position of skin depressors in relation to the heat-generating wires. It should be understood that these numerical indicators could vary even further based upon a variety of engineering principles, materials, intended use and designs incorporated into the invention. The reader is further referred to the above referenced PCT applications, which contain numerous variations on many of the features described herein.

It should be further understood that the individual features described herein can be used together, in the manner above, in a single shaving device. Alternatively, each of the features (or some combination of them) can be used separately, for example, by being added to one of the devices shown in the above referenced PCT publications. Furthermore, it should be understood that the examples given above are exemplary in nature and are not intended to limit the scope of the invention or the claims.

The terms "include", "comprise" and "have" and their conjugates as used herein mean "including but not necessarily limited to".

CLAIMS

1. A hair cutting head, for use in a hair cutting apparatus comprising:
an elongated heated wire suitable for shaving, cutting or burning hair growing from a
5 skin surface; and
a blunt debris removal element, situated and configured to remove debris or scorched
hair residue from the skin after shaving, cutting or burning by the heated wire.
2. A hair cutting head according to claim 1, comprising a row of skin depressing elements
10 on at least one side of said elongated heated wire.
3. A hair cutting head according to claim 2, wherein said at least one side is opposite a
side on which the blunt debris removal element is situated.
- 15 4. A hair cutting head according to any of the preceding claims, wherein said wire has a
diameter between 10 to 1000 micrometers.
5. A hair cutting head according to any of the preceding claims, wherein said wire has a
minimum transverse dimension of between 10 to 500 micrometers.
20
6. A hair cutting head according to any of the preceding claims, wherein said wire has a
minimum transverse dimension of between 500 to 1000 micrometers.
7. A hair cutting device comprising:
25 a hair cutting head according to any of the preceding claims; wherein said wire is heated
when said cutting head comes in contact with a skin surface.
8. A hair cutting device according to any of the preceding claims, wherein said wire is
heated to a temperature between 700 and 800°C.
- 30 9. A hair cutting device according to claim 8, wherein said wire is heated to a temperature
between 800 and 1000°C.

10. A hair cutting head according to claim 8, wherein said wire is heated to a temperature higher than 1000°C.

1/7




FIG.1A




FIG.1B

3/7




FIG. 3

4/7




FIG. 4

5/7




FIG.5A




FIG.5B

6/7




FIG. 5C

7/7




FIG. 6A




FIG. 6B




FIG. 6C

INTERNATIONAL SEARCH REPORT

national Application No

T/IL2004/000602

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A45D26/00 B26B19/00

According to International Patent Classification (IPC) into both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A45D B26B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No
E	WO 2004/080232 A (AZAR ZION ; SHALEV PINCHAS (IL); RADIANCY INC (US)) 23 September 2004 (2004-09-23) page 15, lines 6-25; figures 3,4 -----	1-4,6,8
X	US 1 054 520 A (ELDRIDGE E H) 25 February 1913 (1913-02-25) the whole document -----	1-3
A	US 4 254 324 A (VRTARIC JOHN) 3 March 1981 (1981-03-03) cited in the application column 3, lines 38-66; figures 1,4 -----	1
A	EP 1 269 881 A (HASHIMOTO KENJI) 2 January 2003 (2003-01-02) column 6, line 16 - column 8, line 4; figure 2 -----	1

D Further documents are listed in the continuation of box C



Patent family members are listed in annex

* Special categories of cited documents

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance, the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance, the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

27 October 2004

Date of mailing of the international search report

05/11/2004

Name and mailing address of the ISA

European Patent Office, P B 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel (+31-70) 340-2040, Tx 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Rattenberger, B

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/IL2004/000602

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 2004080232	A	23-09-2004	WO 2004080232 A1	23-09-2004
us 1054520	A		NONE	
us 4254324	A	03-03-1981	NONE	
EP 1269881	A	02-01-2003	JP 3109455 B2	13-11--2000
			JP 11018827 A	26-01--1999
			EP 1269881 A1	02-01--2003
			AU 735061 B2	28-06--2001
			AU 7407198 A	14-01--1999
			CA 2241475 A1	04-01--1999
			CA 2470672 A1	04-01--1999
			DE 69818554 D1	06-11--2003
			DE 69818554 T2	05-08--2004
			EP 0888733 A2	07-01--1999
			US 6043457 A	28-03--2000
			US 6307181 B1	23-10--2001